

ITF COURT PACE CLASSIFICATION PROGRAMME

TECHNICAL DATA SHEET

Brand name	Gerflor® Masters 1000		
Company Name	GERFLOR		
Address	43 boulevard Garibaldi 69170 Tarare		
Telephone	+33 4 74 05 40 00	Fax	+33 4 74 05 04 60
Email	cpoint@gerflor.com	Website	www.gerflor.com

TECHNICAL DATA

GENERAL DESCRIPTION:

Gerflor® Masters 1000 is an acrylic resin tennis surface, suitable for both indoor and outdoor uses. The surface finish provides a Medium-Fast pace bounce, according to the ITF classification. It can be used either for high level tournaments or club practices.

The product can be installed directly on asphalt concrete, plywood panels (for tournaments) and on concrete with a damp proof membrane under the slab.

It is available in a 9 colour range very original and attractive.

The product has been installed at Roland Garros (Indoor National Training Centre), BNP Paribas Masters 2007, 2008 and 2009, St Petersburg Tournament (2008, 2009), Open 13 (2008).

SPECIFICATION OF COURT SURFACE MATERIALS AND CONSTRUCTION, INCLUDING METHOD OF APPLICATION:

Gerflor® Masters 1000 is composed of 3 main layers, a base material can be added depending on the type and the finish aspect of the subfloor.

Primer: helps for the grip of the product on the subfloor

Base layer for application onto new or existing asphalt concrete or concrete.

2 layers of Gerflor® Masters 1000 *Technic*: 2 coats of the acrylic resin reinforced with synthetic fibres and silica sand.

1 layer of Gerflor® Masters 1000 *Finish*: 1 coat of acrylic resin mixed with fine silica sand for a nice finish and the grip expected by tennis players

All the layers are applied with a rubber squeegee.

For the line marking apply one layer of Gerflor® Masters 1000 *Ligne* with a small roller paint brush.

MAINTENANCE GUIDELINES:

Daily: simple sweeping with a broom or vacuumed to remove dust.

Weekly: Machine scrubbed with an adapted brush, water and neutral detergent. Allow to dry

WARRANTY:

This product is guaranteed by the manufacturer to be free from manufacturing defects for 5 years, provided the product is installed by an approved contractor. (Cracks due to the subfloor quality are not included within the guarantee).

Disclaimer. The ITF cannot be held responsible for, and accepts no liability for, the failure of any product or service manufactured, produced or provided according to the information given in this data sheet or for any acts or omissions made in reliance upon it or in connection with it.